

Page 25

[illegible]

29
25

ubb.dom1

Page 26

[illegible]

ANNEXE 2 APPENDIX

30
26
Page 27

```

1 # @BULL_COPYRIGHT@
2 #
3 #
4 # HISTORY
5 # $Log: smtuxadmin.ksh,v $
6 # Revision 1.7 1996/02/12 11:40:49 odeadm
7 # bci V1Set2C 23.01.96
8 # [1996/01/23 14:31:07 dia]
9 #
10 # Revision 1.6 1995/12/20 14:26:59 odeadm
11 # V1 Set2: Still troubles with smtuxadmin.ksh
12 # [1995/12/11 11:56:55 odeadm]
13 #
14 # 07.12.95 V1Set2 first batch of corrections
15 # [1995/12/07 17:22:57 odeadm]
16 #
17 # *** empty log message ***
18 # [1995/11/30 13:48:30 dia]
19 #
20 # *** empty log message ***
21 # [1995/11/30 13:48:30 dia]
22 #
23 # Revision 1.5 1995/10/13 11:52:51 odeadm
24 # Servers TMS/Partitioned mach.
25 # [1995/10/09 12:05:57 dia]
26 #
27 # Revision 1.4 1995/09/15 15:15:06 odeadm
28 # Corrections MRs BUILD 3
29 # [1995/09/07 15:45:27 dia]
30 #
31 # Revision 1.3 1995/08/24 13:38:03 odeadm
32 # Build3
33 # [1995/08/23 09:04:31 odeadm]
34 #
35 # Revision 1.2 1995/07/19 15:18:13 odeadm
36 # Madison build M0.2
37 # [1995/07/10 10:01:58 odeadm]
38 #
39 # $EndLog$
40 #! /bin/ksh
41 ConfDir=$WRAPPING_CONFIGURATION
42 Context=smtuxedo.ctx
43 Scanconf=$MADISON_VAR/surveyor/scanconf.tux
44 V5_to_V4='ROOTDIR=$TUXDIR; export ROOTDIR'
45 Set1_to_Set2='[ -z "$ADMIN" ] && export ADMIN="madison"'
46 cmd=$1; shift
47
48 set_environ() {
49     MASTER=""; APPDIR=""; ADMIN=""
50     filename=$ConfDir/$appname.tux
51     Env=`tuxgetenv -k -v APP_PW $filename << !
52     tuxgetenvp
53     !
54     eval "$Env"; unset APP_PW
55     eval "$Set1_to_Set2"
56     if [ -n "$MASTER" -a -n "$APPDIR" ]
57     then
58         Env="$Env
59 $PW
60 $Set1_to_Set2
61 $V5_to_V4"
62 LD_LIBRARY_PATH=$LIBPATH; export LD_LIBRARY_PATH;
63 cd $APPDIR
64 PATH=${PATH}::$APPDIR:$TUXDIR/bin; export PATH'
65     return 0
66     fi
67     exit 1
68 }
69
70 remote_cmd() {
71     prog="$Env

```

```

72 $cmd"
73 status=?
74 sleep 1
75 echo "\nexit $status"
76
77 #print -r "$prog" > prog
78   rsh "$MASTER" -l "$ADMIN" "$prog" | awk '
79       NR == 1 {line = $0}
80       NR > 1 { print line; line = $0}
81       END {if(sub("^exit ","", line)) exit line; exit -1 }'
82 )
83
84
85 get_tuxconfig() {
86     if [ -s tuxconf.tmp.$appname ]
87     then
88         cat tuxconf.tmp.$appname
89     else
90         rm -f tuxconf.tmp.*
91         prog="$Env"
92 $TUXDIR/bin/tmunloadcf
93 echo "\nexit $?"
94
95 #print -r "$prog" > prog
96   rsh "$MASTER" -l "$ADMIN" "$prog" | tee tuxconf.tmp.$appname
97 fi
98 get_tlistenlog
99 }
100
101 get_tlistenlog() {
102     tllogfname=$ConfDir/tlistenlog.$appname.$machine
103 if [ -s $tllogfname ]
104 then
105     cat $tllogfname
106 else # default value
107     echo "TLLOG $machine $MADISON_TMP/tlisten.$appname.$machine.log" | tee $tllogfname
108 fi
109 echo "\nexit $?"
110 }
111
112 get_tuxval() {
113     get_tuxconfig | \
114     sed -e "s/=//g" -e 's/"//g' -e 's/\\\\/0/g' | awk '
115 BEGIN {
116     tuxconfig_section["*RESOURCES"] = 1
117     tuxconfig_section["*MACHINES"] = 2
118     tuxconfig_section["*GROUPS"] = 3
119     tuxconfig_section["*SERVERS"] = 4
120     tuxconfig_section["*SERVICES"] = 5
121     tuxconfig_section["*ROUTING"] = 6
122     tuxconfig_section["*NETWORK"] = 7
123 }
124 NF == 1 {
125     if ( $1 in tuxconfig_section ) {
126         section = tuxconfig_section[$1]
127         next
128     }
129 }
130 section == 2 && $2 == "LMID" { # MACHINES section
131 if ( $3 == machine) {
132     printf "uname=%s\n", $1
133     mach_found=1
134 }
135 else { # reset mach_found for further machines
136     mach_found = 0
137 }
138 next
139 }
140 section == 2 && $1=="APPDIR" && mach_found==1 {
141     printf "appdir=%s\n", $2
142     appdir = $2

```

~~ANNEXE~~ 2
APPENDIX

32
~~28~~
Page ~~24~~

```
143     next
144   }
145   section == 2 && $1=="TUXCONFIG" && mach_found == 1 {
146     printf "tuxconfig=%s\n", $2
147     next
148   }
149   section == 2 && $1=="TUXDIR" && mach_found==1 {
150     printf "tuxdir=%s\n", $2
151     next
152   }
153   section == 2 && $1=="ROOTDIR" && mach_found==1 { # for V4
154     printf "tuxdir=%s\n", $2
155     next
156   }
157   section == 2 && $1=="ULOGPFX" && mach_found==1 {
158     ulogpfx=1; printf "ulogpfx=%s\n", $2
159     next
160   }
161   section == 7 && NF == 1 {
162     if ( $1 == machine )
163       (mach_found = 1)
164     else { # reset mach_found for other machines
165       mach_found = 0
166     }
167     next
168   }
169   section == 7 && $1=="NLSADDR" && mach_found==1 {
170     printf "nlsaddr=%s\n", $2
171     next
172   }
173   section == 1 && $1 == "UID" {printf "uid=%s\n", $2 ;next }
174   section == 7 && $1=="BRIDGE" && mach_found==1 {
175     printf "bridge=%s\n", $2 }
176   END { # not defined ulogpfx
177     if ( ulogpfx == 0 ) {
178       printf "ulogpfx=%s/ULOG\n", appdir }
179     ' machine=$machine appname=$appname
180     lang=`sed -e "s/=//g" -e "s/'//g" -e "s:// //" $ConfDir/$appname.tux | awk '
181       $1 == "LANG" {printf "lang=", $2}' `
182   }
183
184   get_tllog() {
185     tllogfname="$ConfDir/tllistenlog.$appname.$machine"
186     if [ -f $tllogfname ]
187     then
188       tllog=`cat $tllogfname|awk '$1 == "TLLOG" && $2 == machine { print $3 }' machine=$machine`
189     else
190       tllog="$MADISON_TMP/tllistenlog.$appname.$machine"
191       echo "TLLOG $machine $tllog" > $tllogfname
192   fi
193 }
194
195
196 case $cmd in
197   appli)
198     ls -l $ConfDir 2> /dev/null | awk '
199       sub(".tux$", "", $NF) {print $NF}'
200     ;;
201   isexist)
202     if [ -f $ConfDir/$1.tux ]
203     then
204       echo "Yes"
205     else
206       echo "No"
207     fi
208     ;;
209   setparam)
210     [ ! -d $ConfDir ] && mkdir -p $ConfDir
211     if [ -n "$2" ]
212     then
```

33
29
Page 30

```

213         filename=$ConfDir/$2.tux
214         while [ $# -gt 0 ]
215         do
216             echo "$1=\""$2\""; export $1"
217             shift 2
218         done > $filename
219     fi
220     ;;
221 discover)
222     [ -z "$1" ] && exit 1
223     filename=$ConfDir/$1.tux; shift
224     if [ -f $filename ]
225     then
226         #
227         awk '
228             BEGIN { field = "#promptW:promptP:promptPO:promptS:promptA:pr
229             omptM:promptC:promptR:promptF"; value=":::~::~:" }
230             /\=/ {
231                 for (i=1; i<= NF; i++) {
232                     if(sub("=$", "", $i)) {
233                         separator = ":"
234                         field = field separator $i
235                         value = value separator $(i+1)
236                     }
237                 }
238             }
239             END {
240                 print field; print value
241             }' FS='~'
242         else
243             print '#\n'
244         fi
245     ;;
246 delappname)
247     if [ -n "$2" ]
248     then
249         filename=$ConfDir/$2.tux
250         if [ -f $filename ] && grep -q "$1=[\`"]*$2" $filename
251         then
252             rm -f $filename ${filename}p
253         else
254             echo 'The file does not exist'
255             echo '      or'
256             echo 'The file is not an environment file'
257             exit 1
258         fi
259     fi
260 select)
261     if [ -n "$2" ]
262     then
263         echo "$1='$2'; export $1" > "$Context"
264     fi
265     ;;
266 deselect)
267     rm -f "$Context"
268     ;;
269 selected)
270     APPNAME=""
271     [ -f $Context ] && . ./$Context
272     echo "$1$APPNAME"
273     ;;
274 isselected)
275     rm -f tuxconf.tmp.*
276     [ -f $Context ] && fgrep -q "APPNAME=" $Context && shift
277     echo $1
278     ;;
279 loadcf)
280     appname=$1

```

ANNEXE 2 APPENDIX

34
36
Page 31

loop

```

281 boucle_status=0
282 cmd="\$TUXDIR/bin/tmloadcf -y \$2 \$3"
283 set_environ
284 echo "---- Loading Configuration Binary File ----"
285 remote_cmd
286 status=?
287 if [ \$status -ne 0 ]
288 then
289 exit \$status
290 else
291 # maj fichier \$Scanconf.tux machines
292 prog="\$Env"
293 \$TUXDIR/bin/tmunloadcf
294 echo "\nexit ?"
295
296 #print -r "$prog" > prog
297 rsh "$MASTER" -l "$ADMIN" "$prog" > tuxconf.tmp.$appname
298 list_lmids='cat tuxconf.tmp.$appname | sed -e "s/= /g" -e "s//g" -e "s/\\*//
" | awk '
{line = $0}
$2 == "LMID" && machine == 1 {lmids = lmids $3 " "; next}
$1 == "GROUPS" && $2 == "" { machine=0; next}
$1 == "MACHINES" && $2 == "" { machine = 1; next}
END {if(sub("^exit ","", line)) {
print lmids
exit line}
exit -1 }'
for machine in $list_lmids
do
echo "---- Updating \$Scanconf on $machine ----\n"
get_tuxval > "appname.tux"
../appname.tux
log_prefix='echo $ulogpfx | sed -e 's/. .g' | awk '
(print $NF) '
log_dir='echo $ulogpfx | sed -e 's/. .g' | awk '
{for (i=1; i< NF; i++) {
tempo = tempo "/" $i }}
END { print tempo}'
#Build the 3 lines of \$Scanconf for the application
prog="
[ -x $MADISON_BIN/security/updscantux ] &&
$MADISON_BIN/security/updscantux $appname $log_dir $log_prefix
echo "\\nexit \\$?"
rsh "$uname" -l madison "$prog" | awk '
NR == 1 {line = $0}
NR > 1 { print line; line = $0}
END {if(sub("^exit ","", line)) exit line; exit -1 }'
boucle_status='expr $boucle_status + $?'
done
fi
exit $boucle_status
;;
apppwd)
filename=$ConfDir/$1.tuxp
echo "Enter Application Password: \c"
OLDCONFIG='stty -g'
stty -echo
read APP_PW
echo "\nRe-enter Application Password: \c"
read APP_PW_1
stty $OLDCONFIG
if [ "$APP_PW" != "$APP_PW_1" ]
then
echo "\n\nPassword mismatch!"
echo "Enter any character to exit and retry"
read
else
# PWencode "APP_PW=\"$APP_PW\"; export APP_PW" > $filename
# APP_PW='echo $APP_PW | sed -e "s/'/'\"'\"'/g'
# PWencode "APP_PW='$APP_PW'; export APP_PW" > $filename
tuxgetenv -s > $filename << !

```

ANNEXE 2 **APPENDIX**

35
31
Page 32

```

351 tuxgetenvp
352 $APP_PW
353 !
354         fi
355         ;;
356     chksyntax)
357         appname=$1
358         cmd="\$TUXDIR/bin/tmloadcf -n $2"
359         set_environ
360         remote_cmd
361         exit $?
362         ;;
363     dispIpc)
364         appname=$1
365         cmd="\$TUXDIR/bin/tmloadcf -c $2"
366         set_environ
367         remote_cmd
368         exit $?
369         ;;
370     machine_network)
371         appname=$1
372         set_environ
373         get_tuxconfig | \
374         sed -e "s=/ /g" -e 's/"//g' -e 's/\\//\' -e "s/\*//" | awk '
375             BEGIN { network=0 }
376             {line = $0}
377             NF == 1 { if (network == 1) print $1}
378             $1 == "NETWORK" { network = 1}
379             END {if(sub("^exit ","", line)) exit line; exit -1 }'
380         exit $?
381         ;;
382     machine_machines)
383         appname=$1
384         set_environ
385         get_tuxconfig | \
386         sed -e "s=/ /g" -e 's/"//g' -e 's/\\//\' -e "s/\*//" | awk '
387             BEGIN { machine=0 }
388             {line = $0}
389             $2 == "LMID" { if(machine == 1) print $3}
390             $1 == "GROUPS" { if( $2 == "" ) machine=0}
391             $1 == "MACHINES" { if( $2 == "" ) machine = 1}
392             END {if(sub("^exit ","", line)) exit line; exit -1 }'
393         exit $?
394         ;;
395     group)
396         appname=$1
397         set_environ
398         get_tuxconfig | \
399         sed -e "s=/ /g" -e 's/"//g' -e 's/\\//\' -e "s/\*//" | awk '
400             BEGIN { group=0 }
401             {line = $0}
402             $1 == "SERVERS" { group=0 }
403             $1 == "GROUPS" { if($2 == "") group=1}
404             $2 == "LMID" && $4 == "GRPNO" { if(group) print $1}
405             END {if(sub("^exit ","", line)) exit line; exit -1 }'
406         exit $?
407         ;;
408     svrname)
409         appname=$1
410         set_environ
411         get_tuxconfig | \
412         sed -e "s=/ /g" -e 's/"//g' -e 's/\\//\' -e "s/\*//" | awk '
413             BEGIN { group=server=nb_of_distinct_svr_name=0 }
414             {line = $0}
415             $1 == "TMSNAME" { if ( group == 1) {
416                 trouve = 0
417                 if (nb_of_distinct_svr_name == 0) {
418                     nb_of_distinct_svr_name=1
419                     svr_names[nb_of_distinct_svr_name] = $2
420                     print $2

```


ANNEXE 2 **APPENDIX**

36
32
Page 33

```

422     ) else (
423         for (j=1; j<= nb_of_distinct_svr_name; j++) {
424             if ( $2 == svr_names[j] ) {
425                 trouve=1
426             }
427         }
428         if (trouve == 0) {
429             nb_of_distinct_svr_name += 1
430             svr_names[nb_of_distinct_svr_name] = $2
431             print $2
432         }
433     }
434 }
435
436 $1 == "SERVERS" { if ($2 == "") {
437     server=1
438     group=0 }
439 }
440 $1 == "SERVICES" { if ($2== "") server=0}
441 $1 == "GROUPS"    { if ($2 == "") group=1}
442 $2 == "SRVGRP" {
443     if((server == 1) && ( $4 == "SRVID")) {
444         trouve = 0
445         if (nb_of_distinct_svr_name == 0) {
446             nb_of_distinct_svr_name = 1
447             svr_names[nb_of_distinct_svr_name] = $1
448             print $1
449         } else {
450             for(j=1; j<= nb_of_distinct_svr_name; j++) {
451                 if ( $1 == svr_names[j] ) {
452                     trouve=1
453                 }
454             }
455             if(trouve == 0) {
456                 nb_of_distinct_svr_name += 1
457                 svr_names[nb_of_distinct_svr_name] = $1
458                 print $1
459             }
460         }
461     }
462 }
463 END (if(sub("^exit ", "", line)) exit line; exit -1 )'
464 exit $?
465 ;;
466 svrseq)
467 appname=$1
468 set_enviro
469 get_tuxconfig | \
470 sed -e "s/=//g" -e 's/"//g' -e 's/\\// ' -e "s/\\*//" | awk '
471 BEGIN { server=0; nb_of_distinct_svr_seq=0 }
472 {line = $0}
473 $1 == "SEQUENCE" && server == 1 {
474     trouve = 0
475     if (nb_of_distinct_svr_seq == 0) {
476         nb_of_distinct_svr_seq=1
477         svr_seqs[nb_of_distinct_svr_seq] = $2
478         print $2
479     } else {
480         for (j=1; j<= nb_of_distinct_svr_seq; j++) {
481             if ( $2 == svr_seqs[j] ) {
482                 trouve=1
483             }
484         }
485         if (trouve == 0) {
486             nb_of_distinct_svr_seq += 1
487             svr_seqs[nb_of_distinct_svr_seq] = $2
488             print $2
489         }
490     }
491 }
492 $1 == "SERVERS" { if($2 == "") server=1}

```

~~ANNEXE~~ 2
APPENDIX

37
33
Page 34

```
493         $1 == "SERVICES" { if($2 == "") server=0)
494         END (if(sub("^exit ","", line)) exit line; exit -1 )'
495     exit $?
496     ;;
497 svrId)
498     appname=$1
499     set_environ
500     get_tuxconfig | \
501     sed -e "s/=//g" -e 's//g' -e 's/\\\\/\' -e "s/\\*//"' | awk '
502     BEGIN { server=0; nb_of_distinct_svr_Id=0 }
503     {line = $0}
504     $2 == "SRVGRP" && $4 == "SRVID" && server == 1 {
505         trouve = 0
506         if (nb_of_distinct_svr_Id == 0) {
507             nb_of_distinct_svr_Id=1
508             svr_ids[nb_of_distinct_svr_Id] = $5
509             print $5
510         } else {
511             for (j=1; j<= nb_of_distinct_svr_Id; j++) {
512                 if ( $5 == svr_ids[j] ) {
513                     trouve=1
514                 }
515             }
516             if (trouve == 0) {
517                 nb_of_distinct_svr_Id += 1
518                 svr_ids[nb_of_distinct_svr_Id] = $5
519                 print $5
520             }
521         }
522     }
523     $1 == "SERVERS" { if($2 == "") server=1)
524     $1 == "SERVICES" { if($2 == "") server=0)
525     END (if(sub("^exit ","", line)) exit line; exit -1 )'
526 exit $?
527 ;;
528 discover_conf)
529     machine=$2
530     appname=$1
531     set_environ
532     get_tuxconfig | \
533     sed -e "s/=//g" -e 's//g' -e 's/\\\\/0/' -e "s/\\*//"' | awk '
534     BEGIN {field = "#"}
535     {line = $0}
536     $1 == "UID" {
537         field = field separator $1
538         value = value separator $2
539         separator = ":"
540     }
541     $1 == "GID" {
542         field = field separator $1
543         value = value separator $2
544         separator = ":"
545     }
546     }
547     $1 == "BRIDGE" && network == 1 && mach_found == 1 {
548         field = field separator $1
549         value = value separator $2
550     }
551     $1 == "NLSADDR" && network == 1 && mach_found == 1 {
552         field = field separator $1
553         value = value separator $2
554         network = 0
555         mach_found = 0
556     }
557     $1 == "TLLOG" && $2 == machine {
558         field = field separator $1
559         value = value separator $3
560     }
561     }
562     $1 == machine {mach_found = 1}
563     $1 == "NETWORK" { network = 1}
```

ANNEXE 2
APPENDIX

```
564         END (
565             print field; print value
566             if(sub("^exit ","", line)) exit line; exit -1
567         )' "machine=$machine"
568     exit $?
569     ;;
570 chglisten)
571     appname=$1
572     machine=$2
573     shift 2
574     if [ $# -gt 0 ]
575     then
576         echo "TLLOG $machine $1" > $ConfDir/tlistenlog.$appname.$machine
577     fi
578     exit $?
579     ;;
580 chklistscript)
581     appname=$1
582     machine=$2
583     set_environ
584     get_tuxval > "appname.tux"
585     get_tllog
586     . ./appname.tux
587     prog="
588     if [ -f $appdir/tlisten.$appname.$machine ]
589     then
590         cat $appdir/tlisten.$appname.$machine
591         echo "\\nexit 0\\"
592     else
593         echo "\\nexit 1\\"
594     fi"
595     if [ -z "$uname" ]
596     then
597         print "Host $machine not found"
598         exit 1
599     fi
600     rm -f tlistscript.$appname.$machine
601     rsh "$uname" -l "$ADMIN" "$prog" | tee tlistscript.$appname.$machine > /
602     [ $? -ne 0 ] && exit 1
603     [ -s tlistscript.$appname.$machine ] && cat tlistscript.$appname.$machine |
604     END { if ( $2 == "1" ) exit -1 } '
605     [ $? -eq -1 ] && exit 1
606     [ -s tlistscript.$appname.$machine ] && cat tlistscript.$appname.$machine |
607     awk '
608     $1 ~ "tlisten" {
609         mismatch = 0
610         fexec=sprintf("%s/bin/tlisten", tuxdir)
611         if ($1 != fexec) {
612             print "tlisten command full pathnames mismatch"
613             printf "\\tscript:\\t%s\\n", $1
614             printf "\\tconfig:\\t%s\\n", fexec
615             mismatch +=1
616         }
617         for (i=2; i <= NF; i++) {
618             if (( $i == "-d" ) && ($i+1 != bridge)) {
619                 print "BRIDGE values mismatch"
620                 printf "\\tscript:\\t%s\\n", $(i+1)
621                 printf "\\tconfig:\\t%s\\n", bridge
622                 mismatch +=1
623             }
624             if (( $i == "-l" ) && ($i+1 != nlsaddr)) {
625                 print "NLSADDR values mismatch"
626                 printf "\\tscript:\\t%s\\n", $(i+1)
627                 printf "\\tconfig:\\t%s\\n", nlsaddr
628                 mismatch +=1
629             }
630             if (( $i == "-u" ) && ($i+1 != uid)) {
631                 print "UID values mismatch"
```

~~ANNEXE~~ 2 APPENDIX

39
35
Page 36

```

632         printf "\tscript:\t%s\n", $(i+1)
633         printf "\tconfig:\t%s\n",uid
634         mismatch +=1
635     )
636     if (( $i == "-L" ) && ($(i+1) !=tllog)) {
637         print "LOGFILE values mismatch"
638         printf "\tscript:\t%s\n", $(i+1)
639         printf "\tconfig:\t%s\n", tllog
640         mismatch +=1
641     }
642 })
643 END {
644     if ( mismatch == 0 )
645         printf "Script File is up-to-date for %s\n",machine
646     else
647         printf "\nScript File is NOT up-to-date for %s\n",machine
648     } ' tllog=$tllog machine=$machine bridge=$bridge \
649         nlsaddr=$nlsaddr uid=$uid tuxdir=$tuxdir
650     exit $?
651     ;;
652 startlistproc)
653     appname=$1; shift
654     list="$*"
655     set_environ
656     boucle status=0
657     exit_status=0
658     for machine in $list
659     do
660         echo "\n----- Machine: $machine ----- \n"
661         get_tuxval > "appname.tux"
662         get_tllog
663         . ./appname.tux
664         progl="
665         TUXDIR=$tuxdir; export TUXDIR
666         ROOTDIR=$tuxdir; export ROOTDIR # V4
667         APPDIR=$appdir; export APPDIR
668         TUXCONFIG=$tuxconfig; export TUXCONFIG
669         PATH=${PATH}:\$TUXDIR/bin:\$APPDIR; export PATH
670         LANG=$lang; export LANG
671         LIBPATH=${LIBPATH}:\$tuxdir/lib; export LIBPATH
672         COLUMNS=200; export COLUMNS
673         ps -eF '%u %p %a' | awk '\$3 ~ \"tlisten\" && \$0 ~ \"\$nlsaddr\" {
exit 1)'
674         if [ \ $? = 1 ]
675         then
676             echo "\"Listener already running on $machine\"
677             echo exit 0
678             exit 0
679         fi
680         if [ -f $appdir/tlisten.$appname.$machine ]
681         then
682             . $appdir/tlisten.$appname.$machine
683             ps -eF '%u %p %a' | awk '\$3 ~ \"tlisten\" && \$0 ~ \"\$nls
addr\" (exit 1)'
684             if [ \ $? = 1 ]
685             then
686                 echo "\"Listener started on $machine\"
687                 echo exit 0
688             else
689                 echo "\"Listener starting failed on $machine !!!\"
690                 echo exit 1
691             fi
692         else # create the script file & exec it
693             echo "\"$tuxdir/bin/tlisten -d $bridge -l $nlsaddr -u $uid -L
stllog\" > $appdir/tlisten.$appname.$machine
694             chmod ug+x $appdir/tlisten.$appname.$machine
695             . $appdir/tlisten.$appname.$machine
696             ps -eF '%u %p %a' | awk '\$3 ~ \"tlisten\" && \$0 ~ \"\$nlsadd
r\" (exit 1)'
697             if [ \ $? = 1 ]
698             then

```

(boucle = loop)

ANNEXE 2 APPENDIX

40
36
Page 37

```

699             echo "\"Listener started on $machine\"
700             echo exit 0
701         else
702             echo "\"Listener starting failed on $machine !!!\"
703             echo exit 1
704         fi
705     fi
706     #echo "$progl" > progl
707     if [ -z "$uname" ]
708     then
709         print "Host $machine not found"
710         exit 1
711     fi
712     rsh "$uname" -l "$ADMIN" "$progl" | awk '
713         NR == 1 {line = $0}
714         NR > 1 { print line; line = $0 }
715         END {if(sub("^exit ", "", line)) exit line; print line; exit -1}'
716     boucle_status='expr $boucle_status \|| $?'
717     done
718     exit $boucle_status
719 ;;
720 stoplistproc)
721     appname=$1; shift
722     list="$*"
723     set_environ
724     boucle_status=0
725     exit_status=0
726     for machine in $list
727     do
728         echo "\n----- Machine: $machine -----"
729         get_tuxval > "appname.tux"
730         ../appname.tux
731         progl="
732         COLUMNS=200; export COLUMNS
733         ps -eF '%u %p %a' | awk '\$3 ~ \"tlisten\" && \$0 ~ \"\$nlsaddr\" {print \$
2; exit 0 }' | read pid
734         if [ -n \"$pid\" ]
735         then
736             kill -9 $pid > /dev/null
737             status=$?
738             if [ $status -eq 0 ]
739             then
740                 echo "\"Process $pid killed on $machine\"
741                 echo exit 0
742             else
743                 echo "\"Failed to stop listener on $machine!!!\"
744                 echo exit 1
745             fi
746         else
747             echo "\"No Listener running on $machine\"
748             echo exit 1
749         fi
750         if [ -z "$uname" ]
751         then
752             print "Host $machine not found"
753             exit 1
754         fi
755         rsh "$uname" -l "$ADMIN" "$progl" | awk '
756             NR == 1 {line = $0}
757             NR > 1 { print line; line = $0 }
758             END {if(sub("^exit ", "", line)) exit line; print line; exit -1}'
759         boucle_status='expr $boucle_status \|| $?'
760         done
761     exit $boucle_status
762 ;;
763
764 runninglist)
765     appname=$1
766     boucle_status=0
767     set_environ
768     list_lmids='get_tuxconfig | \

```

ANNEXE 2 APPENDIX

41
37
Page 38

```

769 sed -e "s/= /g" -e 's/"//g' -e 's/\\\\/0/' -e "s/\\+//" | awk '
770 BEGIN { network=0 }
771 {line = $0}
772 NF == 1 { if (network == 1) print $1}
773 $1 == "NETWORK" { network = 1}
774 END (if(sub("^exit ", "", line)) exit line; exit -1 )'
775 for machine in $list_lmds
776 do
777     get_tuxval > "appname.tux"
778     . ./appname.tux
779     prog1="
780     TUXDIR=$tuxdir; export TUXDIR
781     LIBPATH=${LIBPATH}:$tuxdir/lib; export LIBPATH
782     ROOTDIR=$tuxdir; export ROOTDIR # V4
783     APPDIR=$appdir; export APPDIR
784     TUXCONFIG=$tuxconfig; export TUXCONFIG
785     PATH=${PATH}:$TUXDIR/bin:$APPDIR; export PATH
786     LANG=$lang; export LANG
787     COLUMNS=200; export COLUMNS
788     ps -ef '%u %p %a' | awk '\$3 ~ \"tlisten\" && \$0 ~ \"\$nlsaddr\" {print
\\$2}' | read pid
789     if [ -n \"$pid\" ]
790     then
791         echo \"Listener running on $machine: pid = $pid\"
792         echo exit 0
793     else
794         echo \"No Listener running on $machine\"
795         echo exit 0
796     fi
797     if [ -z \"$uname\" ]
798     then
799         print \"Host $machine not found\"
800         exit 1
801     fi
802     rsh \"$uname\" -l \"$ADMIN\" \"$prog1\" | awk '
803     NR == 1 {line = $0}
804     NR > 1 { print line; line = $0}
805     END { if (sub(\"^exit \", \"\", line)) exit line; print line; exit -1) '
806     boucle_status='expr $boucle_status \\| $?'
807 done
808 exit $boucle_status
809 ;;
810 updtlistsript)
811 appname=$1
812 machine=$2
813 set_environ
814 get_tllog
815 get_tuxval > "appname.tux"
816 . ./appname.tux
817 prog="
818 echo \"$tuxdir/bin/tlisten -d $bridge -l $nlsaddr -u Suid -L $tllog\" > $app
dir/tlisten.$appname.$machine
819 chmod ug+x $appdir/tlisten.$appname.$machine
820 echo exit \\$?"
821 if [ -z \"$uname\" ]
822 then
823     print \"Host $machine not found\"
824     exit 1
825 fi
826 rsh \"$uname\" -l \"$ADMIN\" \"$prog\" | awk '
827 NR == 1 {line = $0}
828 NR > 1 { print line; line = $0 }
829 END {if(sub(\"^exit \", \"\", line)) exit line; print line; exit -1)'
830 exit $?
831 ;;
832 tuxBootEnt)
833 appname=$1; shift
834 cmd=\"$TUXDIR/bin/tmboot -y @$\"
835 set_environ
836 remote_cmd
837 exit $?

```

```

838      ;;
839      tuxShutEnt)
840          appname=$1; shift
841          cmd="\$TUXDIR/bin/tmshutdown -y"
842          set_environ
843          remote_cmd
844          exit $?
845      ;;
846      tuxBootAllMach)
847          appname=$1; shift
848          cmd="\$TUXDIR/bin/tmboot -y -A $@"
849          set_environ
850          remote_cmd
851          exit $?
852      ;;
853      tuxShutAllMach)
854          appname=$1; shift
855          cmd="\$TUXDIR/bin/tmshutdown -y -A $@"
856          set_environ
857          remote_cmd
858          exit $?
859      ;;
860      tuxShut)
861          appname=$1; shift
862          cmd="\$TUXDIR/bin/tmshutdown -y $@"
863          set_environ
864          remote_cmd
865          exit $?
866      ;;
867      tuxShutAdmMast)
868          appname=$1; shift
869          cmd="\$TUXDIR/bin/tmshutdown -y -M $@"
870          set_environ
871          remote_cmd
872          exit $?
873      ;;
874      tuxShutSvrSect)
875          appname=$1; shift
876          cmd="\$TUXDIR/bin/tmshutdown -y -S $@"
877          set_environ
878          remote_cmd
879          exit $?
880      ;;
881      tuxBootAdmMast)
882          appname=$1; shift
883          cmd="\$TUXDIR/bin/tmboot -y -M $@"
884          set_environ
885          remote_cmd
886          exit $?
887      ;;
888      tuxBoot)
889          appname=$1; shift
890          cmd="\$TUXDIR/bin/tmboot -y $@"
891          set_environ
892          remote_cmd
893          exit $?
894      ;;
895      tuxShutdown)
896          appname=$2
897          cmd="\$TUXDIR/bin/tmshutdown -y $1"
898          set_environ
899          remote_cmd
900          exit $?
901      ;;
902      tuxBootSvrSct)
903          appname=$1; shift
904          cmd="\$TUXDIR/bin/tmboot -y -S $@"
905          set_environ
906          remote_cmd
907          exit $?
908      ;;

```

```

909     tuxBootBBL)
910         #echo $*
911         appname=$1; shift
912         cmd="\$TUXDIR/bin/tmboot -y $@"
913         set_environ
914         remote_cmd
915         exit $?
916     ;;
917     tuxShowBooted)
918         appname=$1; shift
919         cmd="(echo psr; echo quit)|\$TUXDIR/bin/tmadmin"
920         set_environ
921         remote_cmd
922         exit $?
923     ;;
924     tuxminIPC)
925         appname=$1; shift
926         cmd="\$TUXDIR/bin/tmboot -y -c $@"
927         set_environ
928         remote_cmd
929         exit $?
930     ;;
931     tuxShutPart)
932         exit_status=0
933         appname=$1;
934         machine=$2; shift
935         set_environ
936         get_tuxconfig | \
937         sed -e "s/=//g" -e 's/"//g' -e 's/\\/ /' -e "s/\*//" | awk '
938             $1 == "APPDIR" && mach_section == 1 && mach_found == 1 {
939                 print "APPDIR " $2 > "appname.tux"
940                 mach_section = 0
941                 mach_found = 0
942             }
943             $1 == "TUXCONFIG" && mach_section==1 && mach_found==1 {
944                 print "TUXCONFIG " $2 > "appname.tux"
945             }
946             $1 == "MACHINES" {mach_section = 1}
947             $2 == "LMID" && mach_section == 1 && $3 == machine {
948                 print "MACHINE " $1 > "appname.tux"
949                 mach_found = 1
950             }
951             $1 == "TUXDIR" && mach_section==1 && mach_found==1 {
952                 print "TUXDIR " $2 > "appname.tux"
953             }
954         ' "machine=$machine" "appname=$appname"
955         if [ $? != 0 ]
956         then
957             exit 1
958         fi
959         appdir=`awk ' $1 == "APPDIR" {print $2}' appname.tux`
960         tuxconfig=`awk ' $1 == "TUXCONFIG" {print $2}' appname.tux`
961         uname=`awk ' $1 == "MACHINE" {print $2}' appname.tux`
962         rootdir=`awk ' $1 == "TUXDIR" {print $2}' appname.tux`
963         lang=`sed -e 's/=//g' -e 's/\\/ /g' $ConfDir/$appname.tux |
964             awk ' $1 == "LANG" {print $2}'`
965         prog1="TUXDIR=$rootdir; export TUXDIR
966             APPDIR=$appdir; export APPDIR
967             LIBPATH=${LIBPATH}:$rootdir/lib; export LIBPATH
968             TUXCONFIG=$tuxconfig; export TUXCONFIG
969             LANG=$lang; export LANG
970             PATH=${PATH}:\$TUXDIR/bin:\$APPDIR; export PATH
971             \$TUXDIR/bin/tmshutdown -y -P $@
972             echo \$? > /tmp/rem$appname.$machine.tux"
973         if [ -z "$uname" ]
974         then
975             print "Host $machine not found"
976             exit 1
977         fi
978         rsh $uname -l "$ADMIN" "$prog1"
979         rsh_status=`echo $?`

```


ANNEXE 2 APPENDIX

Page 44
40
41

```

980     if [ "$rsh_status" -eq "0" ]
981     then
982         status=`rsh $uname -l "$ADMIN" "cat /tmp/rem$appname.$machine.tux"`
983         rsh $MASTER -l "$ADMIN" "rm /tmp/rem$appname.$machine.tux" 2> /dev/nul
1   984         rsh $uname -l "$ADMIN" "rm /tmp/rem$appname.$machine.tux" 2> /dev/nul
1   985     fi
986     if [ "$status" -ne "0" ]
987     then
988         exit_status=`expr $exit_status + 1`
989     fi
990     if [ "$exit_status" -ne "0" -o "$rsh_status" -ne "0" ]
991     then
992         exit 1
993     fi
994     ;;
995     loadfshm)
996     appname=$1; machine=$2; shift 2
997     set_environ
998     get_tuxval > "appname.tux"
999     . ./appname.tux
1000     prog="
1001     TUXDIR=$tuxdir; export TUXDIR
1002     ROOTDIR=$tuxdir; export ROOTDIR
1003     LIBPATH=${LIBPATH}:$tuxdir/lib; export LIBPATH
1004     LANG=$lang; export LANG
1005     $tuxdir/bin/loadfiles $@
1006     echo "\"\nexit \${?}\""
1007     if [ -z "$uname" ]
1008     then
1009         print "Host $machine not found"
1010         exit 1
1011     fi
1012     rsh "$uname" -l "$ADMIN" "$prog" | awk '
1013     NR == 1 {line = $0}
1014     NR > 1 { print line; line = $0 }
1015     END {if(sub("^exit ", "", line)) exit line; print line; exit -1}'
1016     ;;
1017     Unloadcf)
1018     appname=$1
1019     set_environ
1020     cmd="\$TUXDIR/bin/tmunloadcf"
1021     if [ $# -eq 2 ]
1022     then
1023         filename=$2
1024         remote_cmd > "$filename"
1025     else
1026         remote_cmd
1027     fi
1028     exit $?
1029     ;;
1030 *)
1031     echo "Command $1 does not exist"
1032     exit 1
1033     ;;
1034 esac

```